

COLORES / COLOURS



Emerald
35x35



Grey
35x35



Pearl
35x35



Turquoise
35x35

PASTA BLANCA — BIII REVESTIMIENTO

Modelo	Size	1	2	3	4	5	6	7	8	9	10	11	12
BRICK RAKU EMERALD 35X35	35x35 14"x14"	Mohs 2	Complies	> 10 %	Complies	> 15 N/mm²	6,7-10-6/°C	Complies	Complies	Class 5	GLA	GHA	GA
BRICK RAKU GREY 35X35	35x35 14"x14"	Mohs 2	Complies	> 10 %	Complies	> 15 N/mm²	6,7-10-6/°C	Complies	Complies	Class 5	GLA	GHA	GA
BRICK RAKU PEARL 35X35	35x35 14"x14"	Mohs 2	Complies	> 10 %	Complies	> 15 N/mm²	6,7-10-6/°C	Complies	Complies	Class 5	GLA	GHA	GA
BRICK RAKU TURQUOISE 35X35	35x35 14"x14"	Mohs 2	Complies	> 10 %	Complies	> 15 N/mm²	6,7-10-6/°C	Complies	Complies	Class 5	GLA	GHA	GA
PENCIL RAKU EMERALD 35X35	35x35 14"x14"	Mohs 2	Complies	> 10 %	Complies	> 15 N/mm²	6,7-10-6/°C	Complies	Complies	Class 5	GLA	GHA	GA
PENCIL RAKU GREY 35X35	35x35 14"x14"	Mohs 2	Complies	> 10 %	Complies	> 15 N/mm²	6,7-10-6/°C	Complies	Complies	Class 5	GLA	GHA	GA
PENCIL RAKU PEARL 35X35	35x35 14"x14"	Mohs 2	Complies	> 10 %	Complies	> 15 N/mm²	6,7-10-6/°C	Complies	Complies	Class 5	GLA	GHA	GA
PENCIL RAKU TURQUOISE 35X35	35x35 14"x14"	Mohs 2	Complies	> 10 %	Complies	> 15 N/mm²	6,7-10-6/°C	Complies	Complies	Class 5	GLA	GHA	GA

1. Mohs scratch hardness (EN 101)

2. Dimensions and surface quality (UNE EN ISO 10545-2)

3. Water absorption (%) (UNE EN ISO 10545-3)

4. Breaking load (N) (UNE EN ISO 10545-4)

5. Flexural strength (N/mm²) (UNE EN ISO 10545-4)

6. Coefficient of linear thermal expansion (UNE EN ISO 10545-8)
7. Thermal shock resistance (UNE EN ISO 10545-9)

8. Crazeing resistance (UNE EN ISO 10545-11)

9. Stain resistance (UNE EN ISO 10545-14)

10. Chemical resistance — weak acids/bases (UNE EN ISO 10545-13)

11. Chemical resistance — strong acids/bases (UNE EN ISO 10545-13)

12. Chemical resistance — household cleaning agents (UNE EN ISO 10545-13)

EMBALAJE / PACKING

Size	Caja / Box			Palé / Pallet			Europalet / EUR		
	PCS	M²	KG	BOX	M²	KG	BOX	M²	KG
35x35 (14"x14")	12	1.47	22.3	0	0	0	36	52.92	828