


COLORES / COLOURS



PORCELÁNICO — BIA PORCELÁNICO

Modelo	Size	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
ROCKSLATE BLACK 60X120	60x120 24"x48"R	Mohs 8	Complies	<0,5%	Complies	> 35N/mm2	Class 3	6,6-10-6/°C	Complies	Complies	Complies	GLA	GHA	GA	Class 5	Class 1	—
ROCKSLATE GREY – ADL 60X120	60x120 24"x48"R	Mohs 2	Complies	<0,5%	Complies	> 35N/mm2	Class 2	6,6-10-6/°C	Complies	Complies	Complies	GLA	GHA	GA	Class 5	Class 3	—
ROCKSLATE GREY 60X120	60x120 24"x48"R	Mohs 8	Complies	<0,5%	Complies	> 35N/mm2	Class 4	6,6-10-6/°C	Complies	Complies	Complies	GLA	GHA	GA	Class 5	Class 1	—
ROCKSLATE-D 60X120	60x120 24"x48"R	Mohs 8	Complies	<0,5%	Complies	> 35N/mm2	Class 3	6,6-10-6/°C	Complies	Complies	Complies	GLA	GHA	GA	Class 5	Class 1	—
ROCKSLATE BLACK 60X60	60x60 24"x24"R	Mohs 8	Complies	<0,5%	Complies	> 35N/mm2	Class 3	6,6-10-6/°C	Complies	Complies	Complies	GLA	GHA	GA	Class 5	Class 1	—
ROCKSLATE GREY 60X60	60x60 24"x24"R	Mohs 8	Complies	<0,5%	Complies	> 35N/mm2	Class 4	6,6-10-6/°C	Complies	Complies	Complies	GLA	GHA	GA	Class 5	Class 1	—

1. Mohs scratch hardness (EN 101)

2. Dimensions and surface quality (UNE EN ISO 10545-2)

3. Water absorption (%) (UNE EN ISO 10545-3)

4. Breaking load (N) (UNE EN ISO 10545-4)

5. Flexural strength (N/mm²) (UNE EN ISO 10545-4)

6. Abrasion resistance (UNE EN ISO 10545-7)

7. Coefficient of linear thermal expansion (UNE EN ISO 10545-8)

8. Thermal shock resistance (UNE EN ISO 10545-9)
9. Cracking resistance (UNE EN ISO 10545-11)

10. Frost resistance (UNE EN ISO 10545-12)

11. Chemical resistance — weak acids/bases (UNE EN ISO 10545-13)

12. Chemical resistance — strong acids/bases (UNE EN ISO 10545-13)

13. Chemical resistance — household cleaning agents (UNE EN ISO 10545-13)

14. Stain resistance (UNE EN ISO 10545-14)

15. Slip resistance (UNE ENV 12633/2003 — DIN 51130/2010)

16. DCOF (DCOF)

EMBALAJE / PACKING

Size	Caja / Box			Palé / Pallet			Europalet / EUR		
	PCS	M²	KG	BOX	M²	KG	BOX	M²	KG
60x120 (24"x48"R)	2	1.44	31.5	0	0	0	30	43.2	970
60x60 (24"x24"R)	3	1.08	21.8	0	0	0	40	43.2	897